

# E Series NV UPS



## Product Snapshot

Power Rating:	400, 600, 800, 1000, 1400, 2000 VA tower models
Voltage:	162 to 290Vac
Frequency:	50/60 Hz (auto-sensing)
Technology:	Line Interactive with Automatic Voltage Regulation

## Introducing the eSeries NV UPS

The E Series® NV line interactive uninterruptible power system (UPS) provides affordable power protection for your personal computers, home, office and other electronic devices. While packed with valuable features such as plentiful power receptacles and USB communications, the compact size is ideal for limited office and home working spaces.

## Features

- Automatic Voltage Regulation (AVR) stabilises fluctuating power sources
- Microprocessor control design ensures high reliability
- Up to four receptacles, allowing easy equipment connection
- User replaceable batteries allow easy maintenance
- Start-on-battery provides portable power capability
- WINPOWER software monitors power conditions and gracefully shuts down computer applications prior to battery depletion
- Intuitive LED indicators display UPS status



Powering Business Worldwide

## E SERIES NV UPS TECHNICAL SPECIFICATIONS - FOR HIGH AND LOW VOLTAGE MODELS

Model	NV 400	NV 600	NV800	NV 1000	NV 1400	NV 2000
VA/Watts	400/240	600/360	800/480	1000/600	1400/840	2000/1200
Model Numbers	ENV400HA	ENV600HA	ENV800HA	ENV1000HA	ENV1400HA	ENV2000HA
Technology	Line Interactive with Automatic Voltage Regulation					

### Input / Output

Input Voltage Window	170~280	160~280	166~280
Output Voltage on Battery	230V		
Frequency	50/60Hz, auto-detection		
Output receptacles	2 ea, 3 pin Aust sockets	4 ea, IEC style (1 output cable included)	
Input Connection	1.8M IEC input cable included		

### Battery

Load	NV 400	NV 600	NV800	NV 1000	NV 1400	NV 2000
100W	10	18	22	35	45	45
120W	7	14	17	-	-	-
200W	-	-	8	14	25	25
400W	-	-	-	6	10	10
600W	-	-	-	-	4	5

Start-On-Battery Unit can be started without being connected to AC utility power -- allows for portable power source

### User Interface

Visual	1 ON / OFF button, 1 indicator LED	1 ON / OFF button, six indicator LED's, including load level
Audible	Five audible alarms indicate operating modes	

### Communications / management

Power Management Software	WINPOWER power management software, downloadable via internet
Connection Type	USB port, with included USB cable

### Approvals

CE marking

### Dimensions and weights

Dimensions (high voltage models)	140 x 100 x 330 mm			205 x 145 x 385 mm		
DiWeight (high voltage models)	5 kg	6 kg	6.5 kg	9.6 kg	10.5 kg	10.6 kg



Eaton Industries Pty. Ltd.  
 Electrical Group  
 Head Office:  
 10 Kent Road Mascot,  
 NSW 2020 Australia  
 1300 UPS UPS (1300 877 877)  
[www.eaton.com/powerquality](http://www.eaton.com/powerquality)

LanSafe, Eaton, ePDU, Flex, PowerChain Management, PowerTrust, Powerware, PowerPass, X-Slot, and PowerVision are trade names, trademarks, and/or service marks of Eaton Corporation. All other trademarks are the property of their respective owners.

© 2008 Eaton Corporation  
 All Rights Reserved  
 Printed in AUS 9135FXA  
 November 2008