

Cisco SRW208MP 8-Port 10/100 Ethernet Switch: WebView/Max PoE Cisco Small Business Managed Switches

Secure, Reliable, Intelligent Switch with PoE for Your Growing Small Business

Highlights

- Connects up to 8 network devices - PCs, printers, and servers - to share and transfer files and videos across your network
- Power over Ethernet easily and cost-effectively powers wireless access points, video cameras, and other network-connected endpoints
- Security down to the switch port level keeps unauthorized users off the network
- Intelligent QoS helps ensure a consistent network experience and supports networked applications including voice, video, and data storage
- Compact size provides multiple placement option for areas with limited space

Figure 1. Cisco SRW208MP 8-Port 10/100 Ethernet Switch: WebView/Max PoE



Product Overview

Growing businesses require cost-effective networking solutions that can scale to meet ever-changing business needs. The Cisco® SRW208MP 8-Port 10/100 Ethernet Switch brings increased intelligence and security to the network infrastructure. Together with its small size, these features make the switch ideal for a conference room or training room where security and uptime are important. It offers two ports for connecting Gigabit copper or optical interfaces to a core switch.

For wireless or voice over IP (VoIP) deployments, the Cisco SRW208MP supports the IEEE 802.3af standard for Power over Ethernet (PoE). With automatic load sensing, the power control circuitry automatically detects PoE on an end device before providing power. Power feeding of Ethernet is limited to the fixed 10BASE-T/100BASE-TX ports. The switch can provide maximum output power per PoE port of up to 15.4W on all eight ports simultaneously. Each port has independent overload and short-circuit protection, with LED indicators for power status.

Network security is a top priority in any size business. Most business data networks, large and small, are unsecured. Unauthorized access to the network and mission-critical data is a constant concern. The Cisco SRW208MP helps secure the network through 802.1X port authentication and

MAC-based filtering. The 802.1X standard requires clients to authenticate themselves before the port will pass data for them.

Businesses are recognizing the benefits of voice over IP (VoIP) and are quickly migrating their voice services to IP-based platforms, requiring their local area networks to support both voice and data applications. In unmanaged IP networks, bursty data sessions can disrupt voice packet delivery, causing poor voice quality. With the enhanced quality of service (QoS) and traffic-management features in the Cisco SRW208MP, voice data can be prioritized, helping ensure clear and reliable voice communications.

The advanced features of the Cisco SRW208MP can help you further secure the integrity of your network. WebView provides an intuitive, highly secure management interface, enabling you to better utilize the comprehensive feature set of the switch, for a better-optimized, more secure network.

Features

- Eight 10/100 switched RJ-45 ports deliver up to 200 Mbps of throughput per port
- Two 10/100/1000 switched RJ-45/mini Gigabit Interface Converter (mini-GBIC) combo ports
- PoE on the 10/100 ports supplies up to the IEEE 802.3af maximum of 15.4W per port on all eight ports
- 5.6-Gbps, nonblocking, store-and-forward switching mechanism
- Simplified QoS management enabled by advanced queuing techniques using 802.1p, differentiated services (DiffServ), or type of service (ToS) traffic prioritization specifications
- Configuration and monitoring from a standard web browser with WebView management
- Secure remote management of the switch via Secure Shell (SSH) and SSL secure channel network protocols
- 802.1Q-based VLANs enable segmentation of networks for improved performance and security
- Private VLAN Edge (PVE) for simplified network isolation of guest connections or autonomous networks
- Automatic configuration of VLANs across multiple switches through Generic VLAN Registration Protocol (GVRP) and Generic Attribute Registration Protocol (GARP)
- Automatic medium dependent interface (MDI) and MDI crossover (MDI-X) detection
- User/network port-level security via 802.1X authentication and MAC-based filtering
- Increased bandwidth (up to 8x) and added link redundancy with Link Aggregation Control Protocol (LACP)
- Enhanced rate-limiting capabilities and storm control, including multicast, broadcast, and flood control
- Port mirroring for noninvasive monitoring of switch traffic
- Jumbo frame support - up to 1632 bytes
- Simple Network Management Protocol (SNMP) versions 1, 2c, and 3
- Fully rack mountable using the included rack-mounting hardware

Specifications

Table 1 contains the specifications, package contents, and minimum requirements for the Cisco SRW208MP 8-Port 10/100 Ethernet Switch.

Table 1. Specifications for the Cisco SRW208MP 8-Port 10/100 Ethernet Switch: WebView/Max PoE

Specifications	
Ports	<ul style="list-style-type: none"> • 8 RJ-45 connectors for 10BASE-T and 100BASE-TX, 2 RJ-45 connectors for 10BASE-T/100BASE-TX/1000BASE-T with 2 Small Form-Factor Pluggable (SFP) slots • Console port • Auto MDI/MDI-X • Auto negotiate/manual setting
Cabling type	Unshielded twisted pair (UTP) Category 5 or better for 10BASE-T/100BASE-TX UTP Category 5 Ethernet or better for 1000BASE-T
LEDs	10/100 Link/Act, PoE, 2 Gig Link/Act, Speed, System
PoE	
802.3af compliant. Supplies up to IEEE Standard maximum of 15.4W on eight 10/100 ports	
Performance	
Switching capacity	5.6 Gbps, nonblocking
Forwarding rate	4.17 mpps wire-speed performance
Layer 2	
MAC table size	8000
Number of VLANs	256 active VLANs (4096 range)
VLAN	<ul style="list-style-type: none"> • Port-based and 802.1Q tag-based VLANs • Management VLAN
Head-of-line (HOL) blocking	HOL blocking prevention
Management	
Web user interface	Built-in web user interface for easy browser-based configuration (HTTP/HTTPS)
SNMP	SNMP versions 1, 2c, and 3 with support for traps
SNMP MIBs	RFC1213 MIB-2, RFC2863 interface MIB, RFC2665 Ether-like MIB, RFC1493 bridge MIB, RFC2674 extended bridge MIB (P-bridge, Q-bridge), RFC2819 RMON MIB (groups 1,2,3,9 only), RFC2737 entity MIB, RFC2618 RADIUS client MIB, RFC1215 traps, private PoE MIB
Remote Monitoring (RMON)	Embedded RMON software agent supports 4 RMON groups (history, statistics, alarms, and events) for enhanced traffic management, monitoring, and analysis.
Firmware upgrade	Web browser upgrade (HTTP) and TFTP
Port mirroring	Traffic on a port can be mirrored to another port for analysis with a network analyzer or RMON probe
Other management	<ul style="list-style-type: none"> • Traceroute • SSL • SSH • RADIUS • Port mirroring • Trivial File Transfer Protocol (TFTP) upgrade • SSL security for web user interface • Dynamic Host Configuration Protocol (DHCP) client • BOOTP • Simple Network Time Protocol (SNTP) • Xmodem upgrade • Cable diagnostics • Ping • Telnet client (SSH secure support)
Security	
IEEE 802.1X	802.1X - RADIUS authentication; MD5 encryption

Access Control	Access control lists (ACLs) - drop or rate limit based on: <ul style="list-style-type: none"> • Source and destination MAC-based • Source and destination IP address • Protocol • ToS/differentiated services code point (DSCP) • Port • VLAN • EtherType
Availability	
Link aggregation	<ul style="list-style-type: none"> • Link aggregation using IEEE 802.3ad LACP • Up to 8 ports in up to 8 groups
Storm control	Broadcast, multicast, and unknown unicast
Spanning Tree	<ul style="list-style-type: none"> • IEEE 802.1d Spanning Tree • IEEE 802.1w Rapid Spanning Tree • IEEE 802.1s Multiple Spanning Tree
Internet Group Management Protocol (IGMP) snooping	IGMP (versions 1 and 2) snooping limits bandwidth-intensive video traffic to only the requestors. Supports 256 multicast groups.
QoS	
Priority levels	4 hardware queues
Scheduling	Priority queuing and weighted round-robin (WRR)
Class of service	<ul style="list-style-type: none"> • Port based • 802.1p VLAN priority based • IPv4/v6 IP precedence/ToS/DSCP based • TCP/ User Datagram Protocol (UDP) port based • DiffServ • Classification and re-marking ACLs
Rate limiting	<ul style="list-style-type: none"> • Ingress policer • Egress rate control
Standards	
<ul style="list-style-type: none"> • 802.3 10BASE-T Ethernet • 802.3u 100BASE-TX Fast Ethernet • 802.3ab 1000BASE-T Gigabit Ethernet • 802.3z Gigabit Ethernet • 802.3x flow control • 802.3ad LACP • 802.3af PoE • 802.1d Spanning Tree Protocol (STP) • 802.1Q/p VLAN • 802.1w Rapid STP • 802.1s Multiple STP • 802.1X port access authentication 	
Environmental	
Dimensions W x H x D	11 x 1.75 x 6.69 in. (279 x 45 x 170 mm)
Unit weight	2.65 lb (1.2 kg)
Power	External AC power adapter
Certification	FCC Part 15 Class A, CE Class A, UL, cUL, CE mark, CB
Operating temperature	0° to 40°C (32° to 104°F)
Storage temperature	-20° to 70°C (-4° to 158°F)
Operating humidity	10% to 90%
Storage humidity	10% to 95%
Package Contents	

<ul style="list-style-type: none"> • Cisco SRW208MP 8-Port 10/100 Ethernet Switch • AC power adapter with power cord • Two rack-mounting kits/eight screws • CD with user guide in PDF format • Registration card • Console cable
Minimum Requirements
<ul style="list-style-type: none"> • Web-based utility: Microsoft Internet Explorer (version 5.5 or later) • Category 5 Ethernet network cables • Operating system: Windows 2000, XP, or later
Product Warranty
5-year limited hardware warranty with return to factory replacement and 90-day limited software warranty

Cisco Limited Warranty for Cisco Small Business Series Products

This Cisco Small Business product comes with a 5-year limited hardware warranty with return to factory replacement and a 90-day limited software warranty. In addition, Cisco offers software application updates for bug fixes and telephone technical support at no charge for the first 12 months following the date of purchase. To download software updates, go to:

<http://www.cisco.com/go/smallbiz>.

Product warranty terms and other information applicable to Cisco products are available at

<http://www.cisco.com/go/warranty>.

For More Information

For more information on Cisco Small Business products and solutions, visit:

<http://www.cisco.com/smallbusiness>.



Americas Headquarters
Cisco Systems, Inc.
San Jose, CA

Asia Pacific Headquarters
Cisco Systems (USA) Pte. Ltd.
Singapore

Europe Headquarters
Cisco Systems International BV
Amsterdam, The Netherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at www.cisco.com/go/offices.

CCDE, CCENT, Cisco Eos, Cisco Lumin, Cisco Nexus, Cisco StadiumVision, Cisco TelePresence, Cisco WebEx, the Cisco logo, DCE, and Welcome to the Human Network are trademarks; Changing the Way We Work, Live, Play, and Learn and Cisco Store are service marks; and Access Registrar, Aironet, AsyncOS, Bringing the Meeting To You, Catalyst, CCDA, CCDP, CCIE, CCIP, CCNA, CCNP, CCSP, CCVP, Cisco, the Cisco Certified Internetwork Expert logo, Cisco IOS, Cisco Press, Cisco Systems, Cisco Systems Capital, the Cisco Systems logo, Cisco Unity, Collaboration Without Limitation, EtherFast, EtherSwitch, Event Center, Fast Step, Follow Me Browsing, FormShare, GigaDrive, HomeLink, Internet Quotient, IOS, iPhone, iQuick Study, IronPort, the IronPort logo, LightStream, Linksys, MediaTone, MeetingPlace, MeetingPlace Chime Sound, MGX, Networkers, Networking Academy, Network Registrar, PCNow, PIX, PowerPanels, ProConnect, ScriptShare, SenderBase, SMARTnet, Spectrum Expert, StackWise, The Fastest Way to Increase Your Internet Quotient, TransPath, WebEx, and the WebEx logo are registered trademarks of Cisco Systems, Inc. and/or its affiliates in the United States and certain other countries.

All other trademarks mentioned in this document or website are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (0809R)