

ProSecure™ Unified Threat Management Appliance **UTM Series**




Unified Gateway Security for Growing Businesses – Without Compromise

The ProSecure UTM series of all-in-one gateway security appliances combine best-of-breed enterprise-strength security technologies from Commtouch®, Mailshell™, and Sophos™ with patent-pending Stream Scanning Technology to protect businesses against today's Web, email, and network threats. Malware hosted on Web pages, phishing attacks, spam, virus infected emails, hackers, denial-of-service attacks, and other threats are now all part of a regular repertoire of sophisticated blended attacks that bypass traditional firewalls with ease. Because comprehensive network security solutions require an abundance of processing power to examine network traffic in real time, existing all-in-one security solutions often use rudimentary security technologies that trade comprehensiveness for speed. True security must satisfy the requirements in both speed and coverage.

All-in-one Network Security - Redefined


ProSecure Unified Threat Management (UTM) Appliances combine performance with comprehensive security coverage. Patent-pending Stream Scanning Technology enables the ProSecure UTM to utilize virus and malware threat databases from ProSecure and Sophos™ that are over one million signatures in size - up to 400x more comprehensive than legacy all-in-one platforms at a speed that is up to 5x faster than conventional methods. This architecture, combined with best-of-breed hybrid in-the-cloud Web filter and anti-spam technologies along with proven firewall, IPS, and VPN functionality, form the ideal growing business gateway security solution.




Revolutionary Stream Scanning Platform

Given the high performance requirements of scanning latency sensitive Web traffic, incorporating enterprise-grade security software technologies onto traditional all-in-one platforms has been a very difficult task. Traditional batch-based scanning methods introduce large amounts of latency into network traffic and can slow Web browsing to a crawl. All-in-one solutions in the past have tried to overcome this by minimizing the malware signature set, scanning only a select few file types, or by avoiding Web scanning altogether. This exposes an entire vector of the network to malware-based attacks. The ProSecure UTM features patent-pending Stream Scanning Technology which analyses data streams as they enter the network. This significantly reduces latency and allows the use of an extensive malware signature library for scanning – thus offering an unprecedented combination of speed and coverage in an all-in-one solution.

Traditional Batch-based Scanning







ProSecure UTM Features and Highlights

Best-of-breed Anti-malware **Engine**

- Enterprise-class malware scan engine
- Up to 400 times the coverage of legacy all-in-one solutions
- Over 1 million malware signatures
- Hourly automatic signature updates
- Zero hour heuristic based threat protection

ProSecure Patent Pending Stream Scanning Technology

- Data streams are processed as they enter the network
- Low latency Web traffic scanning

Distributed Spam Analysis **Anti-spam Technology**

- Hybrid in-the-cloud architecture
- Gathers threat data from over 50 million global sources
- New spam is classified and detected within minutes
- No learning period, works right out of the box
- Minimal false positives

Distributed Web Analysis **URL Filtering**

- Hybrid in-the-cloud architecture
- Hundreds of millions of categorized URLs
- Real-time classification into 64 categories

IM and P2P Application **Control**

- Blocks access to public IM clients
- Blocks peer-to-peer (P2P) clients
- Preserve productivity and save bandwidth













SSL & IPsec VPN Remote Access

- SSL VPN clientless remote access, anywhere, anytime
- IPsec VPN secure site-to-site tunnels and client-based remote access
- No additional licenses to purchase

• Built-in SPI Firewall

- Dual WAN Gigabit Firewall* provides load balancing and failover
- Four Gigabit LAN ports, one configurable hardware DMZ port
- Stateful packet inspection (SPI)
- Denial-of-service (DoS) protection
- IPS prevents hackers from penetrating the network perimeter

Simple Setup, Ease of Management

The ProSecure UTM will easily replace any existing firewall or router. A simple 10-step setup wizard guides you through installation and the UTM will be up and running in minutes. Administration is performed through an intuitive Web-based interface. Set granular policies and alerts, check summary statistics and graphical reports, drill down to IP address-level data, and integrate log data with standard network management tools using SNMP. Malware and IPS signature, software, and firmware updates are all handled by the UTM - online and automatically.

For many administrators and IT personnel one of their biggest nightmares is the management of individual licenses or "seats." Buying additional licenses when computers and personnel are added to the network is time-consuming and costly. The ProSecure UTM offers Web and email protection subscriptions with no "per-user" licensing.

UTM SERIES COMPARISON

MODEL	UTM5	UTM10	UTM25		
SIZING GUIDELINES					
Recommended Number of Concurrent Users	1-5	1-15	10-30		
Average Anti-virus Throughput ¹	15 Mbps	20 Mbps	25 Mbps		
Stateful Packet Inspection Firewall Throughput ¹	90 Mbps	90 Mbps	127 Mbps		
Maximum VPN Throughput ¹	40 Mbps	50 Mbps	70 Mbps		
Maximum Concurrent Connections ¹	8,000	12,000	27,000		
VLANs	255	255	255		
CONTENT SECURITY					
Web and Email Scanned Protocols	HTTP, HTTPS, FTP, SMTP, IMAP, POP3				
Stream Scanning	•	•	•		
Inbound and Outbound Inspection	•	•	•		
Signature-Less Zero Hour Protection	•	•	•		
Malware Signatures	1 Million+	1 Million+	1 Million+		
Automatic Signature Updates	Hourly	Hourly	Hourly		
Web Content Filters	Filter By: HTML Body Keywords, File Extension				
Web Object Filters	ActiveX, Java™, Flash, JavaScript™, Proxy, Cookies				
Email Content Filters	Filter By: Subject Keywords, Password-protected Attachments, File Extension, File Name				
Distributed Spam Analysis	•	•	•		
Distributed Spam Analysis Supported Protocols		SMTP, POP3			
Anti-spam Real-time Blacklist (RBL)	•	•	•		
User-defined Spam Allowed/Block Lists	Filter By: Sender Email Address, Domain, IP Address, Recipient Email Address, Domain				
Distributed Web Analysis w/ 64 categories	•	•	•		
Instant Messaging (IM) Control	MSN® Messenger, Yahoo!® Messenger, mIRC, Google Talk				
Peer to Peer (P2P) Control	BitTorrent™, eDonkey, Gnutella				
Maximum Number of Users	Unlimited				
FIREWALL FEATURES					
Stateful Packet Inspection (SPI)	Port/Service Blocking, Denial-of-service (DoS) Prevention, Stealth Mode, Block TCP Flood, Block UDP Flood, WAN/LAN Ping Response Control				
Intrusion Detection & Prevention (IPS)	•	•	•		
WAN Modes	NAT, Classical Routing				
ISP Address Assignment	DHCP, Static IP Assignment, PPPoE, PPTP				
NAT Modes	1-1 NAT, PAT				
Routing	Static, Dynamic, RIPv1, RIPv2				
VoIP	SIP ALG				

MODEL	UTM5	UTM10	UTM25			
DDNS		DynDNS.org, TZO.com, Oray.net				
Firewall Functions	Port Range Forwarding, Port Triggering, DNS proxy, MAC Address Cloning/spoofing, Network Time Protocol NTP Support, Diagnostic Tools (ping, DNS lookup, trace route, other), Auto-Uplink on Switch Ports, L3 Quality of Service (QoS) ,LAN-to-WAN and WAN-to-LAN (ToS)					
DHCP		DHCP Server, DHCP Relay				
User Authentication for VPN	Active	Directory, LDAP, Radius, Local User D	Database			
PCI Compliance Two Factor Authentication Support	•					
VPN						
Site to Site VPN Tunnels	5	10	25			
Simultaneous SSL VPN Tunnels	2	5	13			
IPsec Encrypton/Authentication	DES.	3DES, AES(128,192,256 bit)/SHA-1	, MD5			
Key Exchange		, Manual Key, Pre-Shared Key, PKI,)				
IPsec NAT Traversal (VPN Passthrough)	IKE, Mariour Rey, Tre-Strated Rey, TRI, X.300					
SSL Version Support	-	SSLv3, TLS1.0	_			
SSL Encryption Support	DES, 3DES, ARC4, AES(128,256 bit)					
SSL Message Integrity	MD5 S	HA-1, MAC-MD5/SHA-1, HMAC-ME	·			
	MD3, 3))/3 A-			
SSL Certificate Support	N.C. 1	RSA, Diffie-Hellman, Self	C V 10 4 :			
SSL VPN Platforms Supported	Window	s 2000 / XP / Vista® (32bit), Mac® O	5 X 10.4+			
DEPLOYMENT						
VLAN Support	•	•	•			
Dual-WAN Fail-over			•			
Intelligent Traffic Load Balancing Based on Traffic Byte Count			•			
Configuration Wizards	Setup, IPsec VPN, SSL VPN					
LOGGING AND REPORTING						
Management	HTTP/HTTPS, SNMP v2c					
Reporting	Summary Statistics, Graphical Reporting, Automatic Outbreak Alerts, Automatic Malware Notifications, System Notifications					
Logging	Traffic, Malware, Spam, Content Filter, Email Filter, System, Service, IPS, Port Scan, IM, P2P, Firewall, IPsec VPN, SSL VPN					
Log Delivery	Management GUI Query, Email Delivery, Syslog					
HARDWARE						
Gigabit RJ45 Ports WAN/LAN	1/4	1/4	2/4			
DMZ Interfaces (Configurable)	1	1	1			
Flash Memory/RAM	2 GB/512 MB	2 GB/512 MB	2 GB/1 GB			
USB Ports	1	1	1			
Certifications	ICSA: Anti-virus VPNC: AES Interop, Basic Interop Checkmark: Anti-Malware, Anti-Spam, Enterprise Firewall, VPN, IPS, URL Filtering					
Major Regulatory Compliance	FCC Class A, CE, WEEE, RoHS					
Storage and Operating Temperatures	Operating Temperature 0°-45° C (32°-113° F), Storage Temperature -20°-70° C (-4°-158° F)					
Humidity	Operation 90% Maximum Relative, Storage 95% Maximum Relative					
Electrical Specifications	100-240V, AC/50-60Hz, Universal Input, 1.2 Amp Max					
Dimensions (W x H x D) cm	33 x 4.3 x 20.9	33 x 4.3 x 20.9	33 x 4.3 x 20.9			
Dimensions (W x H x D) in	13 x 1.7 x 8.2	13 x 1.7 x 8.2	13 x 1.7 x 8.2			
Weight kg/lb	2.1/ 4.6	2.1/ 4.6	2.1/ 4.6			
Package Contents	ProSecure UTM Appliance , Power Cable, Rubber Feet, Resource CD, Rackmount Kit*, Warranty Card, Quick Installation Guide, Subscription Card (Bundles Only)					
Hardware Warranty	2 Years					

ORDERING INFORMATION						
Hardware (Firewall and VPN Functi	onality Only)					
North America		Europe		Asia		
UTM5-100NAS		UTM5-100EUS	UTM5-1		DAJS	
UTM10-100NAS		UTM10-100EUS		UTM10-100AJS		
UTM25-100NAS		UTM25-100EUS		UTM25-100AJS		
1-Year Bundle (Hardware including	I-year Web, 1-yea	ar Email, and 1-year Sof	tware Maintenance and Upg	grades, 24/7	Support, and Advanced Replacement)	
North America		Europe		Asia		
UTM5EW-100NAS		UTM5EW-100EUS		UTM5EW-100AJS		
UTM10EW-100NAS		UTM10EW-100EUS	V-100EUS		UTM10EW-100AJS	
UTM25EW-100NAS		UTM25EW-100EUS	w25EW-100EUS		UTM25EW-100AJS	
3-Year Bundle (Hardware including 3	3-year Web, 3-ye	ar Email, and 3-year Sof	tware Maintenance and Upo	grades, 24/7	Support, and Advanced Replacement)	
North America		Europe		Asia		
UTM5EW3-100NAS		UTM5EW3-100EUS	UTM5EW3-		100AJS	
UTM10EW3-100NAS		UTM10EW3-100EUS		UTM10EW3-100AJS		
UTM25EW3-100NAS		UTM25EW3-100EUS		UTM25EW3-100AJS		
1-Year Subscriptions						
Web Threat Management	Email Threat	Management	Software Maintenance and Upgrades, 24/7 Support, Advanced Replacement		Subscription Bundle (Web + Email + Support & Maintenance)	
UTM5W-10000S	UTM5E-1000	00S	UTM5M-10000S		UTM5B-10000S	
UTM10W-10000S	UTM10E-100	000S	UTM10M-10000S		UTM10B-10000S	
UTM25W-10000S	UTM25E-100	000S	UTM25M-10000S		UTM25B-10000S	
3-Year Subscriptions						
Web Threat Management	Email Threat	Management	Software Maintenance and Upgrades, 24/7 Support, Advanced Replacement		Subscription Bundle (Web + Email + Support & Maintenance)	
UTM5W3-10000S	UTM5E3-100	00S	UTM5M3-10000S		UTM5B3-10000S	
UTM10W3-10000S	UTM10E3-10	0000\$	UTM10M3-10000S		UTM10B3-10000S	

UTM25M3-10000S

UTM25E3-10000S

NETGEAR®

350 E. Plumeria Drive San Jose, CA 95134-1911 1-888-NETGEAR (638-4327) E-mail: info@NETGEAR.com www.NETGEAR.com © 2010 NETGEAR, Inc. NETGEAR, the NETGEAR Logo, NETGEAR Digital Entertainer Logo, Connect with Innovation, FrontView, IntelliFi, PowerShift, ProSafe, ProSecure, RAIDar, RAIDiator, RangeMax, ReadyNAS, Smart Wizard, X-RAID, and X-RAID2, are trademarks and/or registered trademarks of NETGEAR, Inc. and/or subsidiaries in the United States and/or other countries. Mac and the Mac logo are trademarks of Apple Inc., registered in the U.S. and other countries. Other brand names mentioned herein are for identification purposes only and may be trademarks of their respective holder(s). Information is subject to change without notice. All rights reserved.

This product comes with a limited warranty, the acceptance of which is a condition of sale.

UTM25B3-10000S

UTM25W3-10000S

*Available on the UTM25

¹Throughput measured in a lab environment. Actual performance may vary.