5,400 RPM

2.5-Inch SATA Hard Disk Drives





Toshiba's MQ01ABD series offers capacity up to 1TB¹ storage capacity using 500GB per platter technology, enabling the MQ01ABD hard disk drives to speed data processing at higher performance than prior generation products. The 5400 RPM drive series is engineered for energy efficiency and quiet operation, contributing to longer and quieter operation on a single battery charge.

The 500GB-per-platter design, coupled with the benefits of power efficiency and acoustic performance allows PC and consumer electronics devices to provide up to 1TB of capacity with fast performance, minimal heat dissipation and enhanced power utilization in a compact, 2.5-inch form factor. The MQ01ABDseries is ideal for notebook and desktop PCs, mobile workstations, gaming consoles, DVR set-top boxes, external storage solutions and other applications requiring high capacity, durability and cost-effective storage.

The MQ01ABD drive series continues Toshiba Corporation's global commitment to Environmentally Conscious Products (ECPs) that have minimal environmental impact.² As part of this voluntary initiative, Toshiba has reduced or eliminated additional hazardous substances³ in the MQ01ABD drives.

- Up to 1,000GB¹ of Storage Capacity
- 5,400 RPM Rotational Speed
- Advanced Format 512e
- Eco-Conscious Design
- MTTF of 600,000 Hours

Hard



5,400 RPM

2.5-Inch SATA Hard Disk Drives



Series Overview	MQ01ABD025	MQ01ABD032	MQ01ABD050	MQ01ABD075	MQ01ABD100	
	250CP1	220CP1	500CP1	750CP ¹	1 000 CP1	
Drive Capacity Drive Interface	250GB ¹ 320GB ¹ 500GB ¹ 750GB ¹ 1,000GB ¹ Serial ATA, Revision 2.6 / ATA-8					
Number of Platters (disks)	1	1	1	2	2	
Number of Data Heads	2	2	2	4	4	
Sector Size (bytes)			AF 512e ¹			
Transfer Rate to Host			3 Gb/sec			
RoHS Compliant			Yes			
Performance						
Areal Density (max)			744.1 Gb/in ²			
Track-to-track Seek		2 ms				
Average Seek Time			12 ms			
Rotational Speed		5,400 RPM				
Average Latency			5.55 ms			
Buffer Size			8 MB			
Power Requirements						
Voltage			5V (+/- 5%)			
Spin up (start) Power	4.5 watts					
Seek Power	1.85 watts					
Read/Write Power	1.5 watts					
Low Power Idle	0.55 watts					
Standby Power Sleep Power		0.18 watts 0.15 watts				
Physical Sizo						
Physical Size Dimensions (W) x (D) x (H)		60.95 mm (0.75"	\ x 100 0 mm /2 0	4") v 0 5 mm (0 27"	^	
Weight	102 g (3.60 o			4") x 9.5 mm (0.37" oz) 112 g (3.95 oz)	·	
	102 g (0.00 0	z) 102 g (0.00 t	72) 102 g (0.00 c		112 9 (0.00 02	
Environmental						
Temp - Operating	5° to 55°C (41° - 131°F)					
Temp - Non-Operating	-40° to 65°C (-40° - 140°F)					
Vibration - Operating	9.8 m/s² (1.0G) 5 to 500 Hz					
Vibration - Non-Operating	49 m/s ² (5.0G) 15 to 500 Hz					
Shock - Operating	3,920 m/s² (400G) 2ms					
Shock - Non-Operating		8,820 m/s² (900G) 1ms				
Acoustics						
	17 AD	17 dB	17 dB	19 dB	19 dB	
Acoustics (idle) Acoustics (seek)	17 dB 19 dB	19 dB	19 dB	24 dB	24 dB	

Limited Warranty
Limited Warranty

1 year (from date of purchase)

Visit us at: www.toshibastorage.com

global organization that defines internationally-recognized standards for electrical, electronic and associated technologies.

Subject to Change: While Toshiba has made every effort at the time of publication to ensure the accuracy of the information provided herein, product specifications, configurations, prices, system/component/options availability are all subject to change without notice. Product image may represent design model.

 $\ensuremath{\texttt{@}}$ 2012 Toshiba America Electronic Components, Inc. All rights reserved.

¹One Terabyte (1TB) = 1,000 Gigabytes (GB). One Gigabyte (1GB) means 10° = 1,000,000,000 bytes using powers of 10. A computer operating system, however, reports storage capacity using powers of 2 for the definition of $1GB = 2^{30} = 1,073,741,824$ bytes, and therefore shows less storage capacity. Available storage capacity will also be less if the computer includes one or more pre-installed operating systems, pre-installed software applications, or media content. Actual formatted capacity may vary.

²Please refer this site for ECP information: http://www.toshiba.co.jp/env/en/products/index.htm.

³Concentrations of chlorine and bromine are below 900 ppm for each substance, surpassing the IEC61249-2-21:2003 criteria set for printed circuit boards by the International Electrotechnical Commission (IEC), in applying the criteria to all components in the HDD. IEC is the leading