



TruePower New Series

Power Supplies

The Advanced PSU Solution

New features. Same true power. The TruePower New series by Antec offers users an advanced power supply solution, striking the perfect balance of reliability, efficiency and quality. With DC to DC voltage regulator modules, a 120mm PWM fan, and 80 PLUS® Bronze certification, the TP-550, TP-650, TP-750 and TP-750 Blue are the ideal solution for elite system builders and quality-minded enthusiasts alike.



TP-750 Blue:
0761345-23754-3 US
0761345-07663-0 EC
0761345-07664-7 GB
0761345-23755-0 AP



TP-550:
0761345-23552-5 US
0761345-07657-9 EC
0761345-07658-6 GB
0761345-23553-2 AP

TP-650:
0761345-23652-2 US
0761345-07659-3 EC
0761345-07660-9 GB
0761345-23653-9 AP

TP-750:
0761345-23752-9 US
0761345-07661-6 EC
0761345-07662-3 GB
0761345-23753-6 AP

INPUT	
Voltage:	100-240VAC
Frequency Range:	47 Hz to 63 Hz
Current:	
TP-550:	8A @ 115VAC, 4A @ 230VAC
TP-650:	9A @ 115VAC, 4.5A @ 230VAC
TP-750 and TP-750 Blue:	10A @ 115VAC, 5A @ 230VAC
Efficiency:	Min 82% at full load

OUTPUT								
Voltage:	+5V	+3.3V	+12V1	+12V2	+12V3	+12V4	-12V	+5VSB
Max. Load:								
TP-550:	25A	25A	20A	20A	20A	20A	0.8A	3A
TP-650:	25A	25A	22A	22A	25A	25A	0.8A	3A
TP-750 and TP-750 Blue:	25A	25A	25A	25A	25A	25A	0.8A	3A

SPECIFICATION:

- DC to DC voltage regulator modules for greater system stability
- 120mm PWM fan runs up to 50% quieter than standard fans
- Blue internal LED illumination for TP-750 Blue
- Advanced Hybrid Cable Management improves airflow and reduces clutter
- Double layer PCB optimizes cooling efficiency and allows for heavy duty components
- NVIDIA™ SLI™- Ready certified
- 80 PLUS® Bronze certification saves energy and lowers your electric bill
- Universal Input and Active Power Factor Correction
- Supports dual GPUs and dual/quad core CPUs
- 4 + 12V output circuits provide stable power
- ATX12V v2.3 and EPS12V v2.91
- 1 x 6 pin and 1 x 8 (6 + 2) pin PCI-E graphics card connectors for TP-550
- 2 x 6 pin and 2 x 8 (6 + 2) pin PCI-E graphics card connectors for TP-650, TP-750 and TP-750 Blue
- Industrial grade protection
- Safety approval: UL, CUL, CE, CB, FCC Class B, TUV, CCC, C-tick, BSMI
- Weight: 2.3 kg; 5 lbs
- Dimensions: 3.4" (H) x 5.9" (W) x 5.9" (D);
86mm (H) x 150mm (W) x 150mm (D)

