

GP Batteries

Data Sheet

Model No.: GP11A

| | |
|--------------------------|--|
| Description | : Alkaline High Voltage Battery |
| Nominal Voltage | : 6Volts |
| Nominal Dimensions | : Ø10.0mm×16.0mm |
| Terminal | : Nickel plated flat contacts - protruded red(+); recessed black (-) |
| Jacket | : Metal jacket |
| Internal Connection | : Pressure |
| Applications | : Remote controller |
| Average Weight | : 4.0g |
| Date Code | : Unless otherwise specified, each batteries will carry a numeric year code and analogue month code |
| Shelf Life | : Not less than 90% of the service capacity within first year. , not less than 85% of the service capacity with third year storage at 22 ± 3 °C 40-80 %RH. |
| Insulation Resistance | : 5MΩ min. |
| Close Circuit Voltage | : 4.7 Volts (min.)(load resistor 200Ω at 22 ± 3 °C for 0.1 to 2 seconds) |
| Current Drain | Under 15mA pulse, 0.5mA continuous |
| Nominal Service Life | : 74hrs (at 10kΩ load) (to 3.0V at 22 ± 3 °C) |
| Average Service Capacity | : 38mAh(at 10kΩ load) (to 3.0V at 22 ± 3 °C) |

Cross References:

| GP | Eveready | Duracell | Varta |
|-----|----------|----------|-------|
| 11A | --- | --- | --- |

Typical Discharge characteristics at 22 ± 3°C

