

## Tandberg Viking FS-1610 NAS

*Where Smarter Storage Begins*

### The Smarter Choice for Disk-Based Storage

Backup windows are shrinking and rapid file restore is more important than ever. IT departments need storage solutions to meet the increasing demands of users who need to share files in heterogeneous environments.

The Tandberg Viking Series Network-Attached-Storage solutions are designed with this in mind to provide for storage expansion, speedy file access and convenient file sharing for high data availability, rapid recovery, data protection and easy data management.

Powered by Windows® Storage Server™ 2003 R2 (WSS 2003 R2) and optimized for storage-specific management and applications, the Tandberg Viking FS-1610 NAS ensures ease of deployment, flexibility and seamless integration to customers' network environments. Users familiar with the Windows environment will find it very easy to configure the Viking NAS. On top of that, they will not have to worry about the correct number of Client Access License to purchase as the WSS 2003 R2 come with unlimited Client Access License. All file sharing protocols are supported e.g. CIFS/SMB, NFS, AppleTalk, DFS, HTTP & FTP + Storage report manager.

#### Ease of Deployment & Recovery

The Tandberg Viking FS-1610 NAS is relatively easy to deploy without drastic reconfigurations to the network for file-level or block-level access. It also offers quick-restore functionality via Recovery DVD image. It allows user to customize different RAID level for protecting the OS partition. In the event the Viking FS-1610 NAS needs to be restored, the Recovery DVD image brings the Viking FS-1610 NAS back to a factory default in minutes.

#### Easy Backup / Archiving Integration

The Viking FS-1610 NAS offers connectivity support for external tape unit or tape autoloader via its Ultra320 SCSI controller which allows direct connection to a tape device, autoloader or libraries. This makes it the perfect device to further enhance data protection and offline staging for restoration or archival. The Viking FS-1610 NAS can be implemented as a second tiered storage device, a backup server or a centralized file sharing device.

#### S-ATA II Hardware RAID Protection

Using the latest in Serial-ATA HDD technology, Serial-ATA II coupled with hardware RAID, the Viking FS-1610 NAS offers abundant networked storage capacity and performance, and at the same time ensure maximum data availability.



# VIKING

### Reasons To Buy The Tandberg Viking FS-1610 NAS

- 3U form-factor for rack optimized environment
- Powered by Microsoft Windows Storage Server 2003 R2 for flexibility & seamless integration to LAN
- Support up to 16 HDD (or more by adding additional RAID enclosures) using Serial-ATA II connectivity
- Quick installation & configuration using Remote Desktop
- Using DVD image for OS recovery
- Multiple snapshots using Microsoft Shadow Copy Service ensures point-in-time of data recovery
- Hot-Swap Serial-ATA II HDD and hardware RAID provide optimal storage performance & data availability
- Ultra320 SCSI supports for the most demanding external tape device connection in backup & offline archiving operations



Powered by Microsoft Windows  
Storage Server 2003 R2 for  
flexibility & seamless integration  
to LAN

**TANDBERG DATA**   
Securing your Information

## Technical Specifications

Processor	Intel®E5405 Quad-Core Xeon 2.00GHz 12MB Cache (1333 MHz FSB)
Memory	2 GB standard, expandable to 16 GB (667/533 MHz DDR 2)
No. of CPU	1 (Upgradeable to 2)
<b>Storage</b>	
HDD Interface Technology	Serial-ATA II (Hot Swappable)
Number of HDD	16 (maximum 750 GB capacity per HDD Bay or more by adding additional RAID enclosures)
Type of RAID	Hardware Serial-ATA II RAID
RAID level support	RAID 0, 1, 0+1, 3, 5 or 6
<b>Interfaces</b>	
LAN	2 x Auto Sensing Gigabit NICs embedded 10/100/1000 Mbps (RJ45)
SCSI	Dual Channel Ultra320 SCSI LVD/SE
USB	2 x USB 2.0 port
RS232	1 x Serial Port
<b>Expansion Slot</b>	
PCI-Express	1 (x8) PCI-e slot , 1 (x4) PCI-e (using x8) slot
PCI-X	2 x 64bit 100MHz PCI-x (3.3V) slots
PCI	1 x 32bit 33MHz PCI (3.3V) slots
<b>Warranty</b>	
Term	3 years
<b>Dimensions / Weight</b>	
Form factor	3U
Dimensions	H: 5.2" (132mm) x W: 17.2" (437mm) x D: 25.6" (650mm)
Weight	72 lbs (32.7 kg)
<b>Electrical Rating</b>	
Type	Dual-Redundant PSU (Hot Swappable)
Rated Voltage	Auto ranging 100 to 240 VAC @ 50/60 Hz
Rated Current	10 - 14 Amp
Power Consumption	800 W
<b>Environmental Specifications</b>	
Temperature	10°C to 35°C
Relative Humidity	8% - 90% non-condensing
Regulatory Agency Approvals	UL/CB/TUV/CCC/EN 60950/IEC 60950
<b>Operating System</b>	
NAS Operating system	Microsoft®Windows®Storage Server™ 2003 R2
Network File System Protocol	SMB/CIFS, NFS, DFS, Appletalk, HTTP & FTP
Management Interface	Remote Desktop
Management Protocol Support	SNMP, SMTP notification
Environmental Monitoring	Fan, temperature & UPS
Access Control	Active Directory Service, UNIX NIS
Snapshot Technology	Microsoft Volume Shadow Copy Service (VSS)
Backup Software	Windows Backup (or optional 3rd party that supports WSS 2003 R2)
Anti-virus	Optional 3rd party that supports WSS 2003
NAS OS Recovery	DVD Image

For more information, kindly contact your Tandberg Data sales representative or authorised distributor, or visit [www.tandberg.com.sg](http://www.tandberg.com.sg)

**TANDBERG DATA ASIA PTE LTD**  
APAC Head Office  
20 Bendemeer Road #04-05  
Cyberhub Singapore 339914

Tel: +65 6396 0786  
Fax: +65 6396 0787

**TANDBERG DATA**  
BEIJING REP OFFICE  
Room 1003, No. 5 Building  
Jianwai SOHO, No. 39  
East 3rd Ring Road, Chaoyang  
District Beijing 100022  
Tel: +86 10 5126 5288  
Fax: +86 10 5126 5289

**TANDBERG DATA**  
GUANGZHOU REP OFFICE  
Room 2702, South Tower Building,  
Xindacheng Plaza,  
Shuiyinerheng Road, Dongshan district,  
Guangzhou 510620  
Tel: +86 20 8600 0670  
Fax: +86 20 8600 0637

**TANDBERG DATA**  
SHANGHAI REP OFFICE  
Room A201 No. 751  
Yi Chang Road  
Shanghai 200060  
Tel: +86 21 5102 9128  
Fax: +86 21 5102 9129

**TANDBERG DATA**  
INDONESIA REP OFFICE  
Menara Kadin Indonesia  
30/F Jl. H.R. Rasuna Said  
Block X-5, Kav. 2-3  
Jakarta 12950, Indonesia  
Tel: +62 21 5299 4548  
Fax: +62 21 5299 4599

**TANDBERG DATA**  
TAIWAN REP OFFICE  
11F-2 No. 46 Sec.2  
Dunhua S. Road  
Taipei City, 106 Taiwan  
Tel: +886 2 2701 9618  
Fax: +886 2 2701 9620

Specifications subject to change without notice. All product and company names are trademarks or registered trademarks of their respective companies.  
©2007 Tandberg Data. All rights reserved.