

SW SERIES *Simple Weighing Scale*

Commercial Scale



FEATURES

- **Waterproof level IP 66**
- Economic price
- Battery operation with auto power feature
- Large LCD (H=25 mm) display
- 2 kg, 5 kg, 10 kg and 20 kg models available
- Soft touch tack switch
- Compact design & plastic platter
- Small footprint
- Zero, Net, Stable, Low battery designators
- Function
 - SW-1S : On/Off, Zero, Tare, Hold(kg/lb/oz)
 - SW-1C : On/Off, Zero, Tare, Limit function
Counting function

OPTIONS

- AC adapter (9V/300mA)
- Rear display • Waterproof cover



Stainless steel tray



Stainless steel platter

SPECIFICATIONS

Model	SW1S/1C/ 1W - 02	SW1S/1C/ 1W - 05	SW1S/1C/ 1W - 10	SW1S/1C/ 1W - 20	SW1S/1C/ 1W - 30
Capacity / e	2 x0.001kg	5 x0.002kg	10 x0.005kg	20 x0.01kg	30 x0.01kg
Display	110 x35[mm]		5digit LCD		
Symbols	STABLE, ZERO, TARE, g, kg,lb, oz, Low Battery HI/OK/LO & PCS(SW-1C only)				
Keys	ZERO, TARE, HOLD(SW-1S only), MODE(SW-1C only), ON/OFF				
Functions	Water proof level IP 67 (SW-1W only) Weighing Hold Function (SW-1S only) Counting Sample Range : 10~100,200,300,400,500 (SW-1C only) Weight Comparison Function : hi, ok, low (SW-1C only) Weight Unit Conversion Function : kg, lb, oz				
Dimensions	260(W) x287(D) x137(H)[mm] 278(W) x317(D) x141(H)[mm](SW-1W only)				
Platter size	230(W) x190(D)[mm]/ 247(W) x195(D)[mm] (SW-1W only)				
Weight	2.8 kg / 3.8kg(SW-1W only)				
Power	1.5 V x6 units (D size Battery) or 9V Adapter				
MINIMUM VOLTAGE OF THE BATTERY	About 5.8V				
Battery Life	Approx. 800hours (Manganese battery)/ 1600hours (Alkaline at 20°C/68°F)				
Operating Temperature	-10°C ~ +40°C / 14°F ~104°F				