

Phaser 3435DN

Black & White Laser Printer

High-end features,
priced right for your business



Serious performance when quality and productivity count.

Superb output, low cost and reliable. The versatile Phaser 3435 black and white laser printer offers big-business features such as built-in networking, automatic two-sided printing and expansion options. For busy offices and workgroups, the choice is clear.



Affordable, powerful business printer

The Phaser 3435 keeps your office or workgroup functioning at peak performance. Available in network and non-network configurations, this efficient printer delivers impressive, business class documents.

- **33 pages-per-minute** speeds printing of long, A4-size documents.
- **1200 x 1200 dpi output** produces sharp text and graphics.
- **8.5-second first-print-out-time** lessens waiting between print jobs.
- **Automatic two-sided printing** generates professional looking reports and saves paper.
- **400 MHz processor and standard 64 MB memory** handle complex documents without delay.
- **80,000-page maximum monthly duty cycle** meets the requirements for unusually high print demands.



W x D x H:
400 x 435 x 314 mm



More features for peak productivity

- 1 **50-sheet multipurpose tray** accepts envelopes, labels and other thick media as well as custom sizes from 76 x 127 mm to 215.9 x 356 mm.



- 2 **250-sheet paper cassette** adjusts to a variety of sizes, including A4, Letter, Legal, A5 and B5.

- 3 **Optional 250-sheet paper cassette** installs easily and increases total capacity to 550 sheets.



- 4 **Intuitive, two-line LCD control panel** for easy access to the printer menu.



Automatic two-sided printing at 17 impressions-per-minute is ideal for printing reports and saves paper.

64 MB RAM quickly handles complex documents with graphics.

10/100Base-TX interface for workgroup printing.

Centaware Internet Services (IS) shows printer status information and allows configuration of settings via a web browser.

Quality output

Featuring 1200 dpi print resolution, the Phaser 3435 reproduces small text, fine lines and detailed graphics beautifully. Support for Postscript 3 smoothes gradations in graphics such as illustrations and photos.

Built for speed

Fast 33 ppm printing increases office efficiency, especially when printing multi-page documents. Moreover, an 8.5-second first-page-out-time and 15-second warm-up time further enhance speed and productivity.

Workgroup friendly

Add the Phaser 3435 to your workgroup for outstanding productivity. Built-in 10/100Base-TX networking and multi-platform support — including Windows, Mac and Linux — make it perfect for nearly any office.



Specifications of Phaser 3435DN

Print Functions

	Phaser 3435DN
Print Speed	Simplex: Up to 35 ppm (Letter), 33 ppm (A4) Duplex: Up to 17.5 ipm (Letter), 17 ipm (A4)
Print Resolution	Up to 1200 x 1200 dpi effective output
First-Page-Out-Time	As fast as 8.5 seconds
Warm-up Time	Less than 15 seconds
Memory (std/max)	64 MB Flash ROM (includes 4 MB for additional fonts and macros) / 320 MB
Processor	400 MHz
Printer Language	PCL6, PostScript® 3™, IBM ProPrinter, EPSON
Connectivity	Parallel, USB 2.0, Ethernet 10/100Base-TX
Operating System	Windows® 2000/ XP (32/64 bit)/ Vista® (32/64 bit)/Server® 2003 (32/64 bit), Linux® (Ubuntu, Red Hat® 8-9, Fedora Cores 1-4, Mandrake 9.2-10.1, SuSE® 8.2 - 9.2), Mac OS X 10.3-10.5
Input Paper Size	Tray 1 and Tray 2 (optional): Plain Paper -A4, A5, Letter, Legal, Executive, Folio, ISO B5, JIS B5 Multipurpose Tray: Plain Paper - A4, A5, Letter, Legal, Executive, Folio, ISO B5, JIS B5, 3" x 5"; Envelopes - Monarch, No.9, No. 10, DL, C5, C6; Cardstock: Custom size - 76 x 127 mm - 215.9 x 356 mm Duplex: Plain Paper -A4, Letter, Legal, Folio, Officio
Input Paper Weight	Tray 1 and Tray 2 (optional): 60 - 90gsm Multipurpose Tray: Plain Paper 60 - 90gsm; Others 60 - 163gsm Duplex: 75 - 90gsm
Media Input Capacity	Standard: Multipurpose: Tray 50 sheets, Tray: 1 250 sheets Optional: Tray 2: 250 sheets
Media Output Capacity	150 sheets face down
Dimensions (W x D x H)	400 x 435 x 314 mm
Weight	12.7 kg
Power Supply	220 – 240 VAC, 50/60 Hz
Power Consumption	Average: 400W; Power save mode: Less than 11W
Operating Environment	Temperature: 10 °C - 32 °C Humidity: 20 - 80 % RH
Noise Levels	Standby mode: Less than 25dBA; Printing mode: Less than 54dBA
Device Management	Phaser Installer, CentreWare® IS Embedded Web Server, CentreWare Web, Global Print Driver
Warranty	One year on-site warranty



Descriptions in this material, product specifications and/or appearances are subject to change without prior notice due to improvements. Please note that the product colour appears differently from the actual colour as a result of properties of papers or printing ink. Windows and Windows NT are registered trademarks of Microsoft Corporation. NetWare is a registered trademark of Novell, Inc. in the United States. Macintosh, Mac OS and Ether Talk are trademarks of Apple Computer, Inc. PostScript is a registered trademark of Adobe Systems Incorporated in each country. HP-GL is a registered trademark of Hewlett Packard Company. BMLinks is a trademark of the Japan Business Machine and Information System Industries Association (JBMA). Other company names or product names are registered trademarks or trademarks of each company.

Consumables

Print Cartridge (up to 4,000 pages*)	CWAA0762
Print Cartridge (up to 10,000 pages*)	CWAA0763

* Average standard pages. Declared yield in accordance with ISO IEC 19752. Yield may vary depending on image, area, coverage and print mode. Printer is shipped with one starter print cartridge with an average yield of 4,000 pages.

Accessories (optional)

250-sheet Tray	EL300651
32 MB Memory	EL300652
64 MB Memory	EL300653
128 MB Memory	EL300654
256 MB Memory	EL300655

<Reproduction Prohibitions> Please note that reproduction of the following is prohibited by law: Domestic and overseas bank notes and coins, government-issued securities, national bonds and local bond certificates. Unused postage stamps and post cards. Certificate stamps stipulated by law. The reproduction of works for copyright purposes (literary works, musical works, paintings, engravings, maps, cinematographic works, photographic works, etc.) is prohibited except when they are reproduced personally, at home or within limited range according to the above. This product is equipped with an anti-counterfeit feature. This feature is not intended to prevent illegal reproduction. Be extremely careful about the management of equipment used.

 **For Your Safe Use**
Before using the product, read the Instruction Manual carefully for proper use.
Use the product with an appropriate adequate power source and voltage displayed. Be sure to establish a ground.
In the case of a failure or short circuit, an electric shock may result.

For more information or for your nearest authorised Fuji Xerox Printers reseller, visit our website or call:

Australia 1300 793 769
New Zealand 0800 993 769

www.fujixeroxprinters.com.au
www.fujixeroxprinters.co.nz



*XEROX, and the sphere of connectivity design are trademarks or registered trademarks of Xerox Corporation.