



WD Caviar® Green™

Desktop Hard Drives

As hard drive capacities increase, the power required to run those drives increases as well. WD Caviar Green drives make it possible for energy-conscious customers to build systems with higher capacities and the right balance of system performance, ensured reliability, and energy conservation.



INTERFACE

SATA

WIDTH/HEIGHT

3.5-inch/1-inch

ROTATIONAL SPEED

IntelliPower™

CAPACITIES

500 GB to 2 TB

MODEL NUMBERS

WD20EADS	WD7500AADS
WD15EADS	WD6400AADS
WD10EADS	WD6400AACS
WD10EAVS	WD5000AADS
WD10EARS	

Note: Not all products may be available in all regions of the world.

Product Features

Reduced power consumption

WD has reduced power consumption by up to 40 percent compared to standard desktop drives with the combination of WD's IntelliSeek™, NoTouch™, and IntelliPower technologies.

Helps enable eco-friendly PCs

By using environmentally-conscious PCs with our WD Caviar Green drives on board, large organizations with many desktop computers can minimize their carbon footprint and save real money on electricity costs.

Cool and quiet

WD GreenPower Technology™ yields lower operating temperatures for increased reliability and low acoustics for ultra-quiet PCs and external drives.

Perfect for external drives

External drive manufacturers can eliminate the need for a fan in a high-capacity product with a WD Caviar Green drive, the coolest and quietest in its class.

IntelliPower

A fine-tuned balance of spin speed, transfer rate, and caching algorithms designed to deliver both significant power savings and solid performance. Additionally, WD Caviar Green drives consume less current during startup allowing lower peak loads on systems as they are booted.

IntelliSeek

Calculates optimum seek speeds to lower power consumption, noise, and vibration.

NoTouch ramp load technology

The recording head never touches the disk media ensuring significantly less wear to the recording head and media as well as better drive protection in transit.

StableTrac™

The motor shaft is secured at both ends to reduce system-induced vibration and stabilize platters for accurate tracking during read and write operations. (2 TB model only)

Native Command Queuing

Server feature for performance in random I/O transaction environments. It aggregates many small random data transfers and allows the disk to reorder the commands in a sequential order for faster access.

Perpendicular Magnetic Recording

Employs PMR technology to achieve even greater areal density.

Low power spin-up

WD Caviar Green drives consume less current during startup allowing lower peak loads.

Advanced power technology

Electronic components deliver best-in-class low power consumption for reduced power requirements and increased reliability.



PUT YOUR LIFE ON IT®



WD Caviar Green

Specifications ¹	2 TB	1.5 TB	1 TB	1 TB	750 GB	640 GB	500 GB
Model number	WD20EADS	WD15EADS	WD10EADS	WD10EARS	WD7500AADS	WD6400AADS WD6400AACS	WD5000AADS
Interface	SATA 3 Gb/s	SATA 3 Gb/s	SATA 3 Gb/s	SATA 3 Gb/s	SATA 3 Gb/s	SATA 3 Gb/s	SATA 3 Gb/s
Formatted capacity	2,000,398 MB	1,500,301 MB	1,000,204 MB	1,000,204 MB	750,156 MB	640,135 MB	500,107 MB
User sectors per drive	3,907,029,168	2,930,277,168	1,953,525,168	1,953,525,168	1,465,149,168	1,250,263,728	976,773,168
LBA support	Yes	Yes	Yes	Yes	Yes	Yes	Yes
SATA latching connector	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Actuator latch/auto park	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Form factor	3.5-inch	3.5-inch	3.5-inch	3.5-inch	3.5-inch	3.5-inch	3.5-inch
RoHS compliant ²	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Performance							
Data transfer rate (max)							
Buffer to host	3 Gb/s	3 Gb/s	3 Gb/s	3 Gb/s	3 Gb/s	3 Gb/s	3 Gb/s
Host to/from drive (sustained)	110 MB/s	110 MB/s	110 MB/s	111 MB/s	110 MB/s	110 MB/s	110 MB/s
Cache (MB)	32	32	32	64	32	32 (WD6400AADS) 16 (WD6400AACS)	32
Rotational speed (RPM)	IntelliPower	IntelliPower	IntelliPower	IntelliPower	IntelliPower	IntelliPower	IntelliPower
Reliability/Data Integrity							
Load/unload cycles ³	300,000	300,000	300,000	300,000	300,000	300,000	300,000
Non-recoverable read errors per bits read	<1 in 10 ¹⁵	<1 in 10 ¹⁵	<1 in 10 ¹⁵	<1 in 10 ¹⁵	<1 in 10 ¹⁵	<1 in 10 ¹⁵	<1 in 10 ¹⁵
Limited warranty (years) ⁴	3	3	3	3	3	3	3
Power Management							
12VDC (A, peak)	1.759	1.608	1.464	1.75	1.464	1.464	1.206
Average power requirements (W)							
Read/Write	6	4.73	4.9	4.86	4.9	4.9	4.1
Idle	3.7	2.75	2.8	4.85	2.8	2.8	2.2
Standby	0.8	0.72	0.4	0.38	0.4	0.4	0.8
Sleep	0.8	0.72	0.4	0.38	0.4	0.4	0.8
Environmental Specifications⁵							
Temperature (°C)							
Operating	0 to 60	0 to 60	0 to 60	0 to 60	0 to 60	0 to 60	0 to 60
Non-operating	-40 to 70	-40 to 70	-40 to 70	-40 to 70	-40 to 70	-40 to 70	-40 to 70
Shock (Gs)							
Operating (2 ms, read)	30	30	30	30	30	30	30
Operating (2 ms, read/write)	65	65	65	65	65	65	65
Non-operating (1 ms)	250	250	300	300	300	300	350
Average acoustics (dBA) ⁶							
Idle mode	24	24	23	23	23	23	21
Performance seek mode	29	29	27	27	27	27	22
Quiet seek mode	25	25	24	24	24	24	22
Physical Dimensions							
Height (in./mm, max)	1.028/25.4	1.028/25.4	1.028/25.4	1.028/25.4	1.028/25.4	1.028/25.4	1.028/25.4
Length (in./mm, max)	5.787/147	5.787/147	5.787/147	5.787/147	5.787/147	5.787/147	5.787/147
Width (in./mm, ± .01 in.)	4/101.6	4/101.6	4/101.6	4/101.6	4/101.6	4/101.6	4/101.6
Weight (lb./kg, ± 10%)	1.61/0.73	1.61/0.73	1.32/0.60	1.32/0.60	1.32/0.60	1.32/0.60	0.99/0.45

¹ As used for storage capacity, one megabyte (MB) = one million bytes, one gigabyte (GB) = one billion bytes, and one terabyte (TB) = one trillion bytes. Total accessible capacity varies depending on operating environment. As used for buffer or cache, one megabyte (MB) = 1,048,576 bytes. As used for transfer rate or interface, megabyte per second (MB/s) = one million bytes per second, and gigabit per second (Gb/s) = one billion bits per second. Effective maximum SATA 3 Gb/s transfer rate calculated according to the Serial ATA specification published by the SATA-IO organization as of the date of this specification sheet. Visit www.sata-io.org for details.

² WD hard drive products manufactured and sold worldwide after June 1, 2006, meet or exceed Restriction of Hazardous Substances (RoHS) compliance requirements as mandated by the European Union for electrical and electronic products. The RoHS Directive 2002/95/EC of the European Parliament, which is effective in the EU beginning July 1, 2006, aims to protect human health and the environment by restricting the use of certain hazardous substances in new equipment, and consists of restrictions on lead, mercury, cadmium, and other substances.

³ Controlled unload at ambient condition

⁴ The term of the limited warranty may vary by region. Visit support.wdc.com/warranty for details.

⁵ No non-recoverable errors during operating tests or after non-operating tests.

⁶ Sound power level.



Western Digital, WD, the WD logo, WD Caviar, and Put Your Life On It are registered trademarks in the U.S. and other countries; and Blue, Green, Black, IntelliSeek, IntelliPower, NoTouch, WD GreenPower Technology, and FIT Lab are trademarks of Western Digital Technologies, Inc. Other marks may be mentioned herein that belong to other companies. Product specifications subject to change without notice.

© 2009 Western Digital Technologies, Inc. All rights reserved.

Western Digital
20511 Lake Forest Drive
Lake Forest, California 92630
U.S.A.

2879-701229-A10 Oct 2009



For service and literature:

support.wdc.com

www.westerndigital.com

800.ASK.4WDC
800.832.4778
+800.6008.6008
00800.27549338
+31.880062100
North America
Spanish
Asia Pacific
Europe
(toll free where available)
Europe/Middle East/Africa

