

VX1937wm

Enhance productivity and Entertainment

19" WideScreen LCD Monitor VX Series



- > **Fast ClearMotiv® 5ms video response**
Video response as fast as 5ms enables digital HD broadcast-quality video.
- > **100,000:1 Dynamic Contrast Ratio**
Provides for darker black levels and better overall front-of-screen performance.
- > **OptiSync multiple analogue/digital inputs**
Multi-mode input technology supports both digital (DVI-D HDCP) and analogue (VGA) signals for ultimate compatibility and configuration flexibility.
- > **Stylish slim-bezel design**
An ultra-thin bezel lets you see more without taking up valuable desktop real estate.
- > **OnView® controls for superior screen adjustability**
- > **Windows7 certified**
- > **ViewSonic Wizard included**
User-friendly Wizard software automates the setup process to deliver optimized screen performance.
- > **PC and Mac compatible**
- > **ECO Mode**
Environmentally-friendly Eco-mode reduces power consumption and extend backlight life.
- > **SRS Premium Sound**
Extends the speaker frequency range, delivering better response and sound performance.

Model No.	VX1937wm		VX1937wa
LCD	Size Optimum Resolution Brightness (cd/m ²) Contrast Ratio (Typ.) Dynamic Contrast Ratio Viewing Angle (CR 10 / CR 5) Response Time (ms) Pixel Pitch (H x V) Panel Surface Light Source (Hours) Color Support (Millions of colours)	19" wide Color TFT Active Matrix LCD with 16:10 aspect ratio 1440x900 300 1000:1 100,000:1 160° (H), 160° (V) 5ms (Typ) 0.2835 mm (H)x0.2835mm (V) Anti-Glare, Hard coating (3H) 50,000 hrs (Typ.) 16.7 M (6-bits + Hi FRC)	
INPUT	Analog Sync Frequency (Fh / Fv)	RGB Analog (75 ohms, 0.7 / 1.0 Vp-p) Separate Sync / Composite Sync / SOG Fh = 24 ~ 83 kHz ; Fv = 50 ~ 76 Hz, (VGA)	
COMPATIBILITY	PC Mac	VGA up to 1440x900 non-interlaced Power Mac, up to 1440x900	
CONNECTOR	Analog Digital Audio Power	1x15 pin mini D-sub 1xDVI 1x3.5 mm Audio in Built-in power Adapter, 3-Pin plug 2w x2 (SRS Premium Sound)	1x15 pin mini D-sub Built-in power Adapter, 3-Pin plug
SPEAKER	Speaker	Built-in power Adapter, 3-Pin plug	
POWER	Voltage Consumption (W) Save mode (W)	AC 100-240V (Universal); 50/60Hz(Switch) 33 W (typ.) w/o Audio / 48 W (Max) with Audio ≤0.2w	
CONTROLS	Basic OnView / OSD	[1], [2], Power, Down[▼], Up[▲] Auto Image Adjust, Contrast/Brightness, Input Select, D-SUB, DVI, Audio Adjust, Volume, mute, Color Adjust, sRGB, 9300K, 7500K, 6500K, 5000K, User Color [R, G, B], Information , Manual Image Adjust, H/V Position, Horizontal Size, Fine Tune, Sharpness,, Dynamic Contrast, Response Time, Aspect Ratio, Display Mode, ECO Mode, Setup Menu, Language, Resolution Notice, OSD Position, OSD Timeout, OSD Background, Auto Power Off	
OPERATING CONDITIONS	Temperature Humidity (Non condensed)	0 - 40 (°C) / 32 - 104 (°F) 20 - 90 (%)	
DIMENSIONS (WxHxD)	Physical (w/stand)	444.2x374.6x190 (mm), 17.49x14.72x7.48 (in)	
WEIGHT	Net (w/stand)	3.89 kg / 8.58 lb	
REGULATIONS		UL, CUL, FCC-B (ICES), CB, CE, CES-003B, ISO13406-2, TUV/GS, ERGO, TUV-S, NOM, GOST-R, HYGIENIC (20 copies), CCC, BSMI, PSB, C-TICK, KC, SASO, WEEE, RoHS, SASO, Ukraine	
WALL MOUNT (mm)	VESA® Mount Compliant	100mm x 100mm	