

Feature packed in the slimmest IXUS yet at just 17.8mm

Point and Shoot Plus

The IXUS 130 IS is the slimmest IXUS yet. Incorporating a 28mm wide angle lens, 4x Optical Zoom and HD video recording ensures you capture beautiful shots and breathtaking movies. Photography is made easy with all new Smile Smart Shutter, Face Self Timer and Wink Self Timer.



## Key Features

### Precision image quality

- 28mm Wide-angle lens
- Genuine Canon 4x wide-angle Optical Zoom
- Optical Image Stabilizer
- Intelligent Auto (22 scenes detected)
- Intelligent Flash Exposure
- Intelligent Contrast Correction
- Motion Detection Technology
- DiGiC 4 Processor
- 14.1 Megapixel sensor
- Servo AF
- ISO 1600

### Perfect portraits of family & friends

- Smile Smart Shutter
- Wink Self Timer
- Face Detection and Selector
- Face Detection Self-timer
- Red-eye Correction & Blink Detection

### Explore photography and videos made easy

- 2.7" LCD screen
- High Definition Video recording (1280x720)
- My Colours for creative options
- My Category for easy image sorting



**28mm**  
WIDE

### Wide-angle lens

28mm wide-angle lens allows you to shoot beautiful landscapes or capture great group shots

**4x**  
WIDE  
ZOOM

### Get closer to the action

Genuine Canon 4x optical zoom lens (28mm-112mm) to get you closer to the subject



### High Definition Movies (1280x720)

Shoot High Definition movies and view easily on TV with an optional HDMI cable



### Sharper previews

2.7" LCD screen for viewing and sharing your photos



### Intelligent Auto

New Auto mode with Scene Detection, Face Detection, Motion Detection and Noise Reduction makes it even easier to get the perfect shot



### Intelligent Flash Exposure

Automatically detects flash requirements and adjusts the flash output, shutter speed, aperture and ISO speed to best suit the photo being taken



### DiGiC 4 Image Processor

Delivers higher picture quality with faster processing speed



### Quality images

14.1 megapixels deliver outstanding quality images and stunning photo prints up to A2 size



### SDXC Memory Card Compatible

Additionally save all your precious memories to newer high capacity SDXC Memory cards

Tru Capture



# IXUS 130 IS

## Digital Compact Camera

**Canon**  
advanced simplicity®

IXUS

### IXUS 130 IS Technical Specifications

Sensor / Image Processor	
Effective Number of Pixels	Approx. 14.1 MP CCD
Size / Filter Array	1/2.3 inch / Primary colour filter (Bayer)
Processor	DiGiC 4
Lens	
Focal Length (optical)	5.0 (W) – 20.0 (T) mm
35mm film equivalent	28 (W) – 112 (T) mm
f/number	f/2.8 – 8.0 (W), f/5.9 – 17 (T)
Shutter Speed <sup>1</sup>	15 - 1/1500 sec.
Zoom	Optical approx 4x; Digital approx 4x
Image Stabilizer	Optical (Lens Shift Type), approx 3 steps
Focusing	
Focus System	TTL Autofocus
Focusing Frame	Face Detect AiAF <sup>1,2</sup> , Center
Focusing Range	Normal: 5cm – infinity (W), 50cm – infinity (T); Macro: 3cm – 50cm (W)
Shooting Functions	
Face Detection	Auto Focus, Auto Exposure, White Balance, Flash Exposure, Auto Red-Eye correction, Smile Smart Shutter, Wink Self-Timer, FaceSelf-Timer <sup>3</sup> Blink Detection
Other Shooting Features	Servo AF, AF-Point Zoom, Size Select, AF Lock, AF Assist Beam, Intelligent Contrast Correction, Date Stamp, Digital tele-converter, Image Inspection Tool, Night Display
Continuous Shooting (Large/Fine)	Approx 0.8 shots/sec
Self-timer	Approx. 10 sec or 2 sec delay, custom, Wink self-Timer, FaceSelf-Timer
Control/Balance	
Light Metering Method	Evaluative <sup>4</sup> , Centre -weighted average, Spot <sup>5</sup>
Exposure Control Method	Program AE, AE Lock, Intelligent Contrast Correction
Exposure Compensation	± 2 stops in 1/3-stop increments
Sensitivity (Equivalent Film Speed)	Auto <sup>6</sup> , ISO 80/100/200/400/800/1600
White Balance Modes	Auto, Daylight, Cloudy, Tungsten, Fluorescent, Fluorescent H, Custom
LCD Screen	
LCD Screen	2.7 inch Pure Color LCD II monitor with wide viewing angle (approx 230,000 dots)
Flash	
Flash Modes / Functions	Auto, on, off, Auto Red Eye Correction, Red Eye Reduction, Face Detect, Slow Synchro, FE Lock, Intelligent FE
Flash Range	Normal: 30cm – 4.0m (W) 50cm – 2.0 m (T)
Selectable Shooting Modes	
Shooting Modes	Intelligent Auto (with Scene Detection), P, Portrait, Night Snapshot, Kids & Pets, Indoor, Smart Shutter, Low Light, Colour Accent, Colour Swap, Fish-eye Effect, Miniature Effect, Beach, Underwater, Foliage, Snow, Fireworks, Long Shutter, Stitch Assist, Movie (Standard, Colour Accent, Colour Swap)
My Colours	Vivid, Neutral, Sepia, Black & White, Positive Film, Lighter Skin Tone, Darker Skin Tone, Vivid Blue, Vivid Green, Vivid Red, Custom Colour
Image Recording Format	
Still image	JPEG Compression (EXIF 2.2 Compliant)
Colour Space and JPEG Compression	sRGB; Fine, Normal
Movies	MOV (Image Data: H.264; Audio Data: Linear PCM monaural)
Recording Pixels and recording capacity on a 4GB card	
Still Images and Capacity (at Fine Image Setting)	Large: 4320 x 3240 (1058), Medium 1: 3456 x 2592 (1652), Medium 2: 2592 x 1944 (2681), Medium 3: 1600 x 1200 (6352), Small: 640 x 480 (20116), Widescreen: 4320 x 2432 (1403)
Movie Frame Rate	HD 1280x720: 30fps (21min 23sec), 640x480: 30fps (46min 46sec), 320x240: 30fps (2hr 23min 41sec)
Other Operations	
Playback Operations	Red-eye Correction, Enhanced Intelligent Contrast Correction, Trimming, Resize, Slideshow, Index, Magnified, Image Inspection Tool, Advancing and Reversing through magnified images, Auto Rotate, Hints and Tips display, Scroll Display, Histogram, Overexposure Warning, Auto Play, Transition, MyCategory, MyColors, Filter by Date, Smart Shuffle
Direct Printing, PictBridge	Yes <sup>7</sup>
Interface	
Supported Operating Systems	PC: Windows 7, Windows Vista (incl SP1/SP2), XP SP2/SP3; Mac: OS X v10.4 - v10.6
Computer I/F	USB 2.0 Hi-Speed (mini-B compatible), HDMI (mini-connector)
Video Output	PAL or NTSC selectable
Audio Output	Monaural
Memory Storage	SD Memory Card, SDHC Memory Card, SDXC Memory Card, MultiMediaCard, MMCplus card, HC MMCplus card
Menu Languages	26 languages English, German, French, Dutch, Danish, Finnish, Italian, Norwegian, Swedish, Spanish, Simplified Chinese, Russian, Portuguese, Greek, Polish, Czech, Hungarian, Turkish, Traditional Chinese, Korean, Thai, Arabic, Romanian, Ukrainian, Farsi and Japanese
General Features	
Battery	Rechargeable Lithium-ion Battery NB-4L
Shooting Capacity (full charge)	Approx. 230 shots. Playback 6 hours
Dimensions (W x D x H)	92.2 x 56.1 x 17.8 mm
Weight	Approx. 114g (camera body only)

#### Included as Standard

- Rechargeable Lithium-ion Battery NB-4L
- Battery Charger CB-2LVE
- USB Interface Cable IFC-400PCU, AC Cable, AV Cable AVCDC400
- Wrist Strap WS-DC7
- Digital Camera Solution Disc – ZoomBrowser EX (PC), ImageBrowser (Mac), PhotoStitch, CameraWindows

#### Optional Accessories

- AC Adaptor Kit ACK-DC10 (Contains CA-DC10 and DR-10)
- HDMI Cable HTC-100
- High-Power Flash HF-DC1
- Metallic Neck Strap
- Leather Case LCIXUS4
- Waterproof Case WP-DC37



#### Connect, Select Print

Connect your IXUS digital camera to a compatible PIXMA or SELPHY photo printer and print stunning photos at home with the press of a button.

#### Disclaimer

- AF frame can be moved and fixed to specified face
- If no face is detected, AiAF (9 points) is used
- When number of detected faces increases, the shutter is released at 2 sec delay. However if no face is detected for 30 seconds or more, the shooting operation will start automatically.
- Control to incorporate facial brightness in Face Detect AF
- Fixed to center
- Motion Detection - Camera automatically sets the optimal speed according to shooting mode, subject brightness and subject movement and camera shake.
- Compatible printer required for direct printing