

GTECH GSM Gateway



Overview

The GTSIMG04(Mobile Gateway) integrates with your phone system and turns fixed to mobile calls into mobile to mobile calls. The gateway can be connected to most standard Key Telephone Systems or PABX Systems.

Benefits

- Save on call costs
 - Turn Fixed to Mobile calls into Mobile to Mobile calls, thereby in most cases reducing call costs
- Save on Provisioning and Installation costs
 - No need to provision Fixed Lines
 - Easy Installation approx. 20 minutes for a technician to install most systems, no cabling required

Features

- Built in Caller ID
- Superior Voice quality
- High gain antenna options
- Security locks – Network, SIM, PIN lock

Specifications

Module Tri-Band	GSM*/GPRS 900/1800/1900 MHZ
Output Power	Class 4 (2W for GSM 900) Class 1 (1W for GSM 1800)
SIM Interface External	SIM 1.8V & 3V
AT Commands Interface	GSM 07.05 and 07.07
LED Indicator	Power, Network, Signal Strength
Power Supply	Adaptor working on 230V AC
Connectors / Switches	RS 232 Serial port ; SIM Card Holder ; DC Power Socket ; RJ11 connector for Phone ; SMA Antenna Connector ; Power On/Off Switch
Enclosure	ABS Plastic
Mounting	Desktop/ Wall Mounted
Temperature	Operating : 40 C to +50 C Storage : -25 C to +80 C
Certification	CE, A-TICK
Dimensions (mm x mm x mm)	165 L x 135 W x 60 H
Weight	750 Grams
Antenna	SMA Rubber/ 5db Whip
Software	Basic Remote Management Software

